

# Supertex



## Product informatie Product information Information produit Produkt Daten

|   |              |                           |
|---|--------------|---------------------------|
|   | Level        | ●●● SUPER                 |
| Europese classificatie • European classification<br>Classification européenne • Europäische Klassifizierung | EN ISO 10874 | 23 - 32                   |
| Totale dikte • Total thickness<br>Epaisseur totale • Gesamtdicke  | EN ISO 24346 | ca. 3,80 mm               |
| Slijtlaag • Wearlayer<br>Couche d'usure • Nutzschiicht  | EN ISO 24340 | ca. 0,40 mm               |
| Behandeling slijtlaag • Wear layer treatment<br>Traitement couche d'usure • Schutz vor Schmutz              |              | Natural Feel              |
| Totaal gewicht • Total weight<br>Poids total • Gewicht  | EN ISO 23997 | ca. 2400 g/m <sup>2</sup> |

## Formaat & verpakking Size & packing Dimensions & emballage Abmessung & Verpackung

|  |  |            |            |            |
|--|--|------------|------------|------------|
| Breedte • Width<br>Largeur • Breite  |  | 2 m        | 3 m        | 4 m        |
| Standaard lengte • Standard length<br>Longeur standard • Standardlänge                                 |  | ca. 22 m   | ca. 22 m   | ca. 22 m   |
| Standaard rolgewicht • Weight of standard roll<br>Poids standard des rouleaux • Standard-Rollengewicht |  | ca. 110 kg | ca. 165 kg | ca. 220 kg |

## Technische informatie Technical information Information technique Technische Daten

|   |              |  |
|---|--------------|--|
| Antislip • Slip resistance<br>Glissance • Rutschfest  | EN 13893     | DS   |
| Slipweerstand • Sliprestraint<br>Résistance au glissement • Rutschemmung  | DIN 51130    | R11  |
| Brandklasse • Inflammability<br>Classement feu • Brandverhalten   | EN 13501     | Cfl-S1                                       |
| Vloerverwarming • Underfloor heating<br>Chauffage par le sol • Fußbodenheizung  | EN 12524     | Geschikt • Suitable<br>Adapté • Geeignet     |
| Thermische geleidbaarheid • Thermal conductivity<br>Conductivité thermique • Wärmeleitfähigkeit   | EN 12524     | 0,25 W / mK                                  |
| Warmteweerstand • Thermal resistance<br>Résistance thermique • Wärmedurchlasswiderstand   | EN ISO 12466 | 0,0152 m <sup>2</sup> K/W                    |
| Bestendigheid tegen huishoudelijke chemicaliën • Resistance to household chemicals<br>Résistance aux produits d'entretien domestiques • Haushaltschemikalienbeständigkeit | EN ISO 26987 | Zeer goed • Very good<br>Très bon • Sehr gut |
| Garantie • Warranty<br>Garantie • Garantie  |              | 15 jaar • 15 years<br>15 ans • 15 Jahr       |

IVC biedt u garantie tegen fabrieksfouten en vroegtijdige slijtage bij normaal residentieel gebruik. • The warranty covers manufacturing defects and early wear due to normal residential use.  
La garantie couvre les erreurs de fabrication et l'usure précoce lors d'un emploi normal résidentiel. • Die Garantie gewährleistet Fabrikationsfehler und frühzeitiges Abnutzen in normalen Wohnbereich

