

Pescara Tiles

Tuft gauge	1/10 loop pile		ISO 2424
Pilecomposition	100% PA SDN		ISO 2424
Primary Backing	Non Woven		ISO 2424
Secondary backing	Bitumen		ISO 2424
Width	50 x 50 cm	± 0.2%	EN 984
Pile Weight	550 gr/m ²		ISO 8543
Total weight	Bitumen : 4000 gr/m ²	± 15%	ISO 8543
Pile height	2 mm		ISO 1766
Total Height	Bitumen : 5 mm		ISO 1765
Number of knots	181.240/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1		EN 13501-1
Use Area	Heavy project use (33)		EN 1307
GUT Nr.	00EBE12F GUT		www.pro-dis.info
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Electrostatic charging	<2 kV		ISO 6356
Luxury class	LC1		EN 1307
Comments	Installation designs; Monolithic, Quarter turn, Brick, Ashlar, Random.		
Pictures	www.condorcontract.com		

Floorsymbols



Certificates

CE
 2020
 Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-022RBP164
 Reaction to fire:
 Bfl-s1
 Slip resistance: DS
 Bitumen
 Resilient floor
 covering to be
 used within a
 building

