

## Romance Elite

<b>Tuft gauge</b>	1/8 cut pile	ISO 2424
<b>Pilecomposition</b>	100% PP	ISO 2424
<b>Primary Backing</b>	Woven	ISO 2424
<b>Secondary backing</b>	AB, Felt	ISO 2424
<b>Width</b>	400 cm ± 1%	EN 984
<b>Pile Weight</b>	1800 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	AB : 2700 gr/m <sup>2</sup> Felt : 2800 gr/m <sup>2</sup>	± 15% ISO 8543
<b>Pile height</b>	15 mm ± 2 mm	ISO 1766
<b>Total Height</b>	AB : 17 mm Felt : 18 mm	ISO 1765
<b>Fire Classification</b>	Efl	EN 13501-1
<b>Use Area</b>	Heavy domestic use (23)	EN 1307
<b>Light fastness</b>	≥ 5	105-B02
<b>Wearebility</b>	≥ 4	105-X12
<b>Water fastness</b>	≥ 4	105-E01

## Floorsymbols



## Certificates



Condor Carpets  
Euroweg 3  
8061 SB Hasselt  
EN1307

DOP: C-001AR157

Reaction to fire:  
Efl

Slip resistance: DS  
AB

Resilient floor  
covering to be  
used within a  
building



Condor Carpets  
Euroweg 3  
8061 SB Hasselt  
EN1307

DOP: C-001FR157

Reaction to fire:  
Efl

Slip resistance: DS  
Felt

Resilient floor  
covering to be  
used within a  
building



www.blauer-engel.de/uz128

