




PRODUCT SPECIFICATION					DATE: 19/05/11
PRODUCTNAME: COMMERCIAL : BOUNTY REALBACK PRODUCTION : Index SC volbad + realback CODE : 059 002 098					 EN 14041  
COLOURS/FARBEN 1192;3365;9890;9891;9892;9895;9896;9897;9899;9903;9904 COLORIS/KLEUREN:					
WIDTH/BREITE/LARGEUR/BREEDTE: 2 m 4 m LENGTH/LÄNGE/LONGUEUR/LENGTE: 40 m 40 m					
REMARKS/BEMERKUNGEN/REMARQUES/OPMERKINGEN: minimum order quantity = 1 standard unit					EN 13297
TECHN. INFORM.	TECHN. DATEN	CAR.TECHN.	TECHN. GEGEV.	NORM	
MANUFACTURING PROCESS	HERSTELLUNGS-ART	TECHN. DE FABRICATION	FABRICATION-METHODE	DIN61151	needle-felt
SURFACE ASPECT	OBERFLÄCHEN-STRUKT.	ASPECT DU SURFACE	POOL-STRUCTUUR		ribbed
PILE COMPOSITION	POL MATERIAL	COMP. DU POIL	POOL-MATERIAAL		75% Polyprop - 25 % Polyester
PILE WEIGHT	POLGEWICHT	POIDS DU POIL	POOLGEWICHT	ISO8543	250gr/m2 ± 10%
PILE HEIGHT	POLHÖHE	HAUT. DU POIL	POOLHOOGTE		1,5mm ± 10%
PRIM. BACKING	PRIM. RÜCKEN-AUSSTATTUNG	DOSSIER PRIM.	PRIM. BACKING	ISO2424	Styr. But. Latex + adhesive
SEC. BACKING	SEC. RÜCKEN-AUSSTATTUNG	DOSSIER SEC.	SEC. BACKING	ISO2424	needle-felt
BACKING WEIGHT	RÜCKEN-GEWICHT	POIDS DU SUPPORT	BACKING-GEWICHT		390gr/m2 ± 10%
TOTAL WEIGHT	GESAMTGEWICHT	POIDS TOTAL	TOTAALGEWICHT	ISO8543	640gr/m2 ± 10%
TOTAL HEIGHT	GESAMTHÖHE	HAUTEUR TOT.	TOT. HOOGTE	ISO1765	4,6mm ± 10%
TECHN. INFORM.	TECHN. DATEN	CAR.TECHN.	TECHN. GEGEV.	NORM	
PERMANENT ANTISTATIC	PERMANENT ANTISTATISCH	ANTISTATIQUE PERMANENT	PERMANENT ANTISTATISCH	ISO6356	
TO/RUBBING	REIBECHTHEIT	AU FROTTEM.	WRIJFECHTH.	ISO105X12	4 Except for 9903 3
CLASSIFICATION	KLASSIFIKATION	CLASSIFICATION	CLASSIFICATIE		
FLAMMABILITY	BRAND-VERHALTEN	COMPORTEMENT AU FEU	BRANDGEDRAG	EN 13501-1	Efl- fully adhesive
USAGE	ANWENDUNG	EMPLOI	GEBRUIK		domestic
Due to limitations of the manufacturing process, colour may slightly vary from batch to batch. We reserve the right to alter technical specifications.	Durch dem Produktions Prozess bedingt, können geringe Farbabweichungen von Partie zu Partie auftreten. Wir behalten uns das Recht um die Technischen Daten zu ändern.	Du à des limitations de production, le coloris peut varier légèrement d'une production à l'autre. Le fabrication se réserve le droit de modifier les caractéristiques techniques.	Door beperkingen in het productieproces, zijn geringe kleurafwijkingen van partij tot partij mogelijk. Wij behouden het recht de technische gegevens aan te passen.		