

Adoration

Tuft gauge	1/8 cut pile		ISO 2424
Pilecomposition	100% PP		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB, Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1200 gr/m ²		ISO 8543
Total weight	AB : 2050 gr/m ² Felt : 2100 gr/m ²	± 15%	ISO 8543
Pile height	11,5 mm	± 2 mm	ISO 1766
Total Height	AB : 13,5 mm Felt : 14,5 mm		ISO 1765
Number of knots	126.080/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Efl		EN 13501-1
Use Area	Medium domestic use (22)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates

 2019 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001AA136 Reaction to fire: Efl Slip resistance: DS AB Resilient floor covering to be used within a building	 2019 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FA136 Reaction to fire: Efl Slip resistance: DS Felt Resilient floor covering to be used within a building
---	---


www.blauer-engel.de/uz128





