

## BINGO

|                              |  |                           |
|------------------------------|--|---------------------------|
| <b>Manufacturing process</b> | Tufted   | ISO 2424                  |
| <b>Gauge</b>                 | 5/32" Loop   |                           |
| <b>Pilecomposition</b>       | 100% PP  | ISO 2424                  |
| <b>Primary backing</b>       | Woven PP   | ISO 2424                  |
| <b>Secondary backing</b>     | AB + Felt  | ISO 2424                  |
| <b>Width</b>                 | 400 cm, 500 cm   | ± 1%<br>EN 986            |
| <b>Pile weight</b>           | approx. 370 gr/m <sup>2</sup>  | ISO 8543                  |
| <b>Total weight</b>          | AB : approx. 1410 gr/m <sup>2</sup><br>Felt : approx. 1430 gr/m <sup>2</sup> | ± 15%<br>ISO 8543         |
| <b>Pile height</b>           | approx. 4,0 mm   | ISO 1765                  |
| <b>Total height</b>          | AB : approx. 6,0 mm<br>Felt : approx. 6,5 mm                                 | + 15% / -10%<br>ISO 1765  |
| <b>Number of knots</b>       | approx. 90.900 /m <sup>2</sup>   | + 10% / -7,5%<br>ISO 1763 |
| <b>Fire classification</b>   | AB : Cfl-S1 verlijmd<br>Felt : Efl   | EN 13501-1                |
| <b>Light fastness</b>        | ≥ 5  | 105-B02                   |
| <b>Wearability</b>           | ≥ 4  | 105-X12                   |
| <b>Water fastness</b>        | ≥ 4  | 105-E01                   |
| <b>Thermal resistance</b>    | 0,120 m <sup>2</sup> K/W   | ISO 8302                  |
| <b>Sound insulation</b>      | 10,0 dB  | ISO 10140                 |
| <b>GUT Nr.</b>               | AB : 89ECF791<br>Felt : 4CC94928   |                           |

### Floorsymbols AB



### Floorsymbols Felt



### Certificates

