

## Nelson

<b>Tuft gauge</b>	1/4 loop pile		ISO 2424
<b>Pilecomposition</b>	100% Wool		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	AB, Felt		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 984
<b>Pile Weight</b>	1000 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	AB : 1800 gr/m <sup>2</sup> Felt : 1850 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	5 mm	± 2 mm	ISO 1766
<b>Total Height</b>	AB : 7 mm Felt : 9 mm		ISO 1765
<b>Number of knots</b>	43175/m <sup>2</sup>	-7.5% . +10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1	EN 13501-1	
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>GUT Nr.</b>	49F1AB0E GUT		www.pro-dis.info
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates



2013

Condor Carpets  
Euroweg 3  
8061 SB Hasselt

EN1307

DOP: C-027AN095

Reaction to fire:  
Cfl-s1  
1658

Slip resistance: DS

AB

Resilient floor  
covering to be  
used within a  
building



2013

Condor Carpets  
Euroweg 3  
8061 SB Hasselt

EN1307

DOP: C-027FN095

Reaction to fire:  
Cfl-s1  
1658

Slip resistance: DS

Felt

Resilient floor  
covering to be  
used within a  
building

