

Piccadilly Speciaal

| | | | |
|----------------------------|-------------------------------|-------------|----------|
| Tuft gauge | 1/10 cut pile | | ISO 2424 |
| Pilecomposition | 100% PP | | ISO 2424 |
| Primary Backing | Woven | | ISO 2424 |
| Secondary backing | Felt | | ISO 2424 |
| Width | 400 cm | ± 1% | EN 984 |
| Pile Weight | 1600 gr/m ² | | ISO 8543 |
| Total weight | Felt : 2600 gr/m ² | ± 15% | ISO 8543 |
| Pile height | 18 mm | ± 2 mm | ISO 1766 |
| Total Height | Felt : 20 mm | | ISO 1765 |
| Number of knots | 118500/m ² | -7.5% .+10% | ISO 1763 |
| Fire Classification | Efl | EN 13501-1 | |
| Use Area | Heavy domestic use (23) | | EN 1307 |
| Light fastness | ≥ 5 | | 105-B02 |
| Wearebility | ≥ 4 | | 105-X12 |
| Water fastness | ≥ 4 | | 105-E01 |

Floorsymbols



Certificates



2023

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-001FP178

Reaction to fire:
Efl

Slip resistance: DS

Felt

Resilient floor
covering to be
used within a
building



www.blauer-engel.de/uz128

