



# REWIND<sup>®</sup>

## CONTRACT 900 FLAT



TECHNICAL DATA	TECHNISCHE DATEN	FICHE TECHNIQUE		
Manufacturing process	Herstellungsart	Méthode de fabrication	DIN 61151	Needle felt
Surface structure	Oberflächenstruktur	Aspect de surface	-	Flat
Pile material	Polmaterial	Composition des fibres	-	100% polypropylene
Pile weight Total weight	Polgewicht Gesamtgewicht	Poids des fibres Poids total	ISO 8543	900 g/m <sup>2</sup>
Roll length	Rollenlänge	Longueur rouleau	-	30 m
Backing	Rückenbeschichtung	Dossier	ISO 2424	None - latex free
Pile height	Polhöhe	Hauteur du velours	ISO 1765	5 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	5 mm
Permanent anti-static	Permanent antistatisch	Antistatique permanent	ISO 6356	≤ 2kV
Fire Classification	Brennklasse	Comportement au feu	EN 13501-1	Bfl-s1
Thermal resistance	Thermische Beständigkeit	Résistance thermique	ISO 8302	0,0832 m <sup>2</sup> K/W
Impact noise reduction	Trittschallminderung	Réduction du bruit d'impact		20 dB
Resistance to rubbing	Reibechtheit	Résistance au frottement	ISO 105X12	≥ 5
Prodis GUT Certificate	Prodis GUT Zertifikat	Certificat Prodis GUT	-	



### CONTACT

rewind@bintg.com  
www.rewindcarpet.com

A BRAND OF  
**Beaulieu  
International  
Group**



# REWIND® 900 FLAT

COLOUR NAME		2M	4M
1098	PEBBLE	✓	✓
2077	CARBON	✓	✓
2158	STORM GREY	✓	✓
2190	ANTHRACITE	✓	✓
2225	STEEL GREY	✓	✓
2241	SILVER	✓	✓
2266	CHARCOAL	✓	✓
3088	RUBY RED	✓	✓
5100	MIDNIGHT	✓	✓
5131	NILE BLUE	✓	✓
5151	JEANS	✓	✓
6099	FOREST	✓	✓
6125	DARK OLIVE	✓	✓
7001	FOX	✓	✓
7055	DESERT	✓	✓
7104	DEEP BROWN	✓	✓

