

Structura

| | | |
|----------------------------|-------------------------------------|------------|
| Tuft gauge | 1/10 cut pile | ISO 2424 |
| Pilecomposition | 100% PP | ISO 2424 |
| Primary Backing | Non Woven | ISO 2424 |
| Secondary backing | Felt | ISO 2424 |
| Width | 400 cm ± 1% | EN 984 |
| Pile Weight | 800 gr/m ² | ISO 8543 |
| Total weight | Felt : 1800 gr/m ² ± 15% | ISO 8543 |
| Pile height | 5 mm ± 2 mm | ISO 1766 |
| Total Height | Felt : 8 mm | ISO 1765 |
| Number of knots | 237000 /m ² -7.5% .+10% | ISO 1763 |
| Fire Classification | Efl | EN 13501-1 |
| Use Area | Heavy domestic use (23) | EN 1307 |
| Light fastness | ≥5 | 105-B02 |
| Wearebility | ≥4 | 105-X12 |
| Water fastness | ≥4 | 105-E01 |

Floorsymbols



Certificates



2024

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-027FG009

Reaction to fire:
Cl-s1
I658

Slip resistance: DS

AB

Resilient floor
covering to be
used within a
building