

Rimini

Tuft gauge	1/10 cut pile		ISO 2424
Pilecomposition	100% PP		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB, Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	400 gr/m ²		ISO 8543
Total weight	AB : 1300 gr/m ² Felt : 1350 gr/m ²	± 15%	ISO 8543
Pile height	5.5 mm	± 2 mm	ISO 1766
Total Height	AB : 7.5 mm Felt : 8.5 mm		ISO 1765
Number of knots	122.140/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Efl		EN 13501-1
Use Area	Medium domestic use (22)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates



2015

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-001AR126

Reaction to fire: Efl

Slip resistance: DS
AB

Resilient floor covering to be used within a building



2015

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-001FR126

Reaction to fire: Efl

Slip resistance: DS
Felt

Resilient floor covering to be used within a building

